



# Omni Electrical and Lighting Australia

10B Kelly Ct  
 Springvale VIC 3171  
 Tel:1300 333 001 Fax:1300 333 002  
 E-mail:sales@omni-au.com

## Data Sheet



Model No	LLFM-100WPS-CCT	LLFM-200WPS-CCT
Body Colour	Black	Black
Body Material	Aluminium	Aluminium
Diffuser	Glass	Glass
Colour Temp	3000/4500/6500K	3000/4500/6500K
Voltage	AC90-305V	AC90-305V
Frequency	50/60Hz	50/60Hz
Wattage	50W/80W/100W selectable	120W/150W/200W selectable
Beam Angle	120°	120°
Lumen	8500/13600/17000LM	20400/25500/34000LM
PF	>0.9	>0.9
CRI	>80	>80
Dimmable	No	No
IP Rating	IP66	IP66
Life Time	50000 HRS	50000 HRS
LED Chip	LUMILED SMD2835	LUMILED SMD2835
Power Cable	1.20m Flex&Plug	1.20m Flex&Plug
Installation	Surface mounting	Surface mounting
Warranty	5 Years	5 Years
Size(D/H-mm)	270*342	320*390
Net Weight	2.84KG	4.21KG
Packing	5 pcs /Carton	4 pcs /Carton